### R RASCO

# RASCO IMPLEMENTS FOR SMALL MULTIFUNCTIONAL VEHICLES







### Contents

- Street sweeping
- De-icing and anti-icing
- Snow clearing
- Street washing
- Grass cutting
- Trash collection & material transport



# Street sweeping & washing

### SX2

### MUVO vacuum sweeper





### **KEY CHARACTERISTICS**

- Provides MUVO vehicle with capabilities of compact sweeper machine
- MUVO chassis designed specifically for optimal placement of hose leading from suction mouth to garbage hopper
- 4 stars EUnited PM2.5 certificate

- Extremely powerful suction system
- Great operating visibility
- Garbage hopper can be used as water tank in combination with washers instead of front brushes

Garbage hopper volume	1,6 m <sup>3</sup>
Water tank volume	300 L
Standard cleaning width	max. 2200 mm
Cleaning speed	cca. 1,5 10 km/h















## SX 1200 / 1600

Holder/Multihog vacuum sweeper



### **KEY CHARACTERISTICS**

- Designed for Multihog and Holder vehicles
- 4 stars EUnited PM2.5 certificate

- Powerful suction system
- Great operating visibility

	SX 1200	SX 1600
Waste container capacity	1,2 m <sup>3</sup>	1,6 m <sup>3</sup>
Fresh water tank capacity	220 L	280 L
Standard sweeping width	max. 20	000 mm
Working speed	cca. 1,5 –	10,0 km/h







# De-icing and anti-icing

## SOLID XG

Small multifunctional vehicles spreader with auger conveyor





### **KEY CHARACTERISTICS**

- Designed for wide range of small multifunctional vehicles
- Dry spreading or pre-wetting
- Auger conveyor for solid material transport
- Reliable & constant material distribution
- Speed-dependant spreading

- Large capacity
- High spreading precision & efficiency
- Easy control of spreading parameters

Volume of solid agent hopper	0,6 – 1,5 m <sup>3</sup>
Volume of liquid agent tanks	300 - 500 L
Spreading width	1 – 6 m
Transport system	Auger







# LIQUID S

Brine sprayer





### **KEY CHARACTERISTICS**

- Uses liquid agent for spraying
- High capacity liquid pumps
- Modular tanks for stability in transport
- Speed-dependant spreading

- Reduced spreading agent consumption
- Can operate at higher speeds than conventional spreader
- Easy control of spreading parameters

Volume of liquid agent tanks	1500 – 2500 L
Spreading width	2 or 3 m fixed
	2 – 6 m variable



### MRP

Tailgate spreader





### **KEY CHARACTERISTICS**

- Mounting on rear end of TKS tipper body
- Dry spreading only
- Manual spreading pattern adjustment (adjustment via linear motor optional)

- Very quick mounting / demounting
- Simple operation & minimal maintenance
- Easy to refill with spreading material

Volume of dry agent hopper	0,37 m <sup>3</sup>
Spreading width	1 – 6 m
Spreading quantity	0 - 300 g/m <sup>2</sup>







# Snow clearing

### BILO

Small multifunctional vehicles single-segment snow plough



### **KEY CHARACTERISTICS**

- Clears snow up to 30 cm
- Obstacle passing mechanisms
- Left-right swiveling

- Robust and durable
- Simple to control
- Usable on sensitive surfaces (when equipped with rubber or polyurethane scrapers)

Width at the scrapers	1600 – 2400 mm
Wing height	750 mm
Rotation angle	30°
Number of scraper segments	4/5
Scraper types	steel, rubber, polyurethane







## VERTUS G

Small multifunctional vehicles variable geometry snow plough



### **KEY CHARACTERISTICS**

- Clears snow up to 30 cm
- Obstacle passing mechanisms
- Independently movable wings

- Great for gathering snow into heaps
- Simple to control
- Usable on sensitive surfaces (when equipped with rubber scrapers)

Width at the scrapers	1600 – 2400 mm
Wing height internal / external	660 / 800 (750 / 920) mm
Rotation angle	40°
Number of scraper segments	4
Scraper types	steel, rubber







## MKM

Muvo front brush





### **KEY CHARACTERISTICS**

- Clears snow up to 10 cm
- Left-right swiveling
- Variable rotation speed
- Optional water sprinkling nozzle bar

- Very thorough surface clearing
- Usable in all seasons
- Prevents damage to surfaces

Total width	1930 – 2330 mm
Sweeping width	1600 – 2000 mm
Brush segment radius	550 mm
Rotation angle	30°







### MKH

### Small multifunctional vehicles front brush



### **KEY CHARACTERISTICS**

- Clears snow up to 10 cm
- Left-right swiveling
- Variable rotation speed
- Motors enclosed inside axle

- Very thorough surface clearing
- Usable in all seasons
- Prevents damage to surfaces
- Very compact dimensions

Total width	1200 – 1600 mm
Sweeping width	1040 - 1380 mm
Brush segment radius	600 mm
Rotation angle	30°



# Street washing

## WBT

### Muvo washing bar





Nozzle bar width	1500 mm
Left-right swiveling	30°
Water pump flow	max. 100 L/min
Water pump pressure	max. 40 bar



# WBH

### Muvo telescopic washing bar





Nozzle bar width	1500 – 2350 mm
Left-right swiveling	30°
Water pump flow	max. 150 L/min
Water pump pressure	max. 50 bar





## SV 2.0

### Muvo water tank





Capacity 2000 L

Anti-splashing barriers inside tank



# Grass cutting

### KKM

### Muvo front crane mower





### **KEY CHARACTERISTICS**

- Weight relief and floating position systems
- Crane arm slides along guide rail for quick obstacle avoidance
- Can be swiveled to work either on the right-hand or left-hand side of the vehicle

- Robust & durable mowing head with spiral blade layout for highly efficient mowing
- Designed for long periods of uninterrupted operation
- User-friendly controls

Mower reach	4000 mm
Mowing head width	1000 mm
Counterweight	750 kg













# Trash collection & material transport

### KK 3.0

#### Muvo trash container





Capacity 2,7 m<sup>3</sup>
Emptying mechanism for 120/240 L trash bins









### M3

#### Muvo skiploader





Payload

3,0 t

For containers with base width up to 1100 mm









## TKS

### Muvo three-sided tipper body



Dimensions (L x W x H)	1810 x 1247 x 400 mm
Volume (to top of side walls)	903 L
Tipping angle toward the rear	53°
Tipping angle to the side	47°









www.rasco.hr rasco@rasco.hr facebook.com/rasco youtube.com/rasco linkedin.com/rasco